



Ø6.3 [0.25"]
OUTLET HOLE

0.87" [22.10] A/F

1/8" NPT
MALE THRD.

1.69" [42.80]

NEXFLOW™

1/8" NPT
FEMALE THRD.

Front view

THIRD ANGLE PROJECTION		REQUIREMENTS—UNLESS OTHERWISE SPECIFIED		CONTRACT NUMBER —		NEX FLOW AIR PRODUCTS CORP.				
		GENERAL		CLIENT —	CONTRACTOR —	10520 YONGE STREET, UNIT 35B-220, RICHMOND HILL, ON L4C 3C7 TEL.: (416) 410-1313 & FAX: (416) 410-1806 www.nex-flow.com				
MATERIAL	SS-304	1. DIMS ARE IN INCHES (MM) 2. DIMENSIONING AND TOLERANCING IN ACCORDANCE WITH ANSI Y14.5 (1982) 3. MACHINE FINISH 125 MICRO INCH RMS 4. INTERNAL RADII .015 5. BREAK SHARP CORNERS .005 TO .015		DRAWN CHIRAG.S	DATE 30/05/2015	TITLE				
FINISH		—	LIMITS		DESIGN —	CHECKED ASHISH	1/8" STAINLESS STEEL SWIVEL FITTING			
		1. LINEAR DIMS. .XXX = .005 .XX = .010 .X = .030 2. ANGLES = 3: 1/2" 3. RUNOUT .010 TIR 4. HOLES IN ACCORDANCE WITH AND 10387		PROJECT —	CL.A. —	SIZE	CAGE CODE	PART NO.	RELEASE	REV
				STRESS —	MANUFACTURING —	—	—	90052	—	—
				THERMAL —	MATERIALS —	SCALE	CAD NO	SHEET	OF	
				MECHANISM —	ELECTRICAL —	1:1		1	1	