

PROPRIETARY
REPRODUCTION OR DISTRIBUTION WITHOUT WRITTEN CONSENT OF NEXFLOW™ IS PROHIBITED.

THIRD ANGLE PROJECTION

MATERIAL: ALUMINIUM

FINISH: BLUE ANODIZED

NEXT ASSEMBLY	USED ON	QTY PER ASSY	PART NO
PART NO			

REQUIREMENTS–UNLESS OTHERWISE SPECIFIED

GENERAL

1. DIMS ARE IN INCHES (MM).
2. DIMENSIONING AND TOLERANCING IN ACCORDANCE WITH ANSI Y14.5 (1982)
3. MACHINE FINISH 125 MICRO INCH RMS
4. INTERNAL RADII .015" (0.4)
5. BREAK SHARP CORNERS .005" (0.1) TO .015" (0.4)

LIMITS

1. LINEAR DIMS.
   .XXX = .005" (0.1)
   .XX = .010" (0.3)
   .X = .030" (0.8)
2. ANGLES = ± 1/2°
3. RUNOUT .010 TIR
4. HOLES IN ACCORDANCE WITH AND 10387

CONTRACT NUMBER	–
CLIENT	–
CONTRACTOR	–
DRAWN	CHIRAG.S
DATE	21/06/2018
DESIGN	LES
CHECKED	ASHISH
PROJECT	–
Q.A.	–
STRESS	–
MANUFACTURING	–
THERMAL	–
MATERIALS	–
MECHANISM	–
ELECTRICAL	–

NEX FLOW AIR PRODUCTS CORP.
10520 YONGE STREET, UNIT 358–220, RICHMOND HILL, ON L4C 3C7
TEL.: (416) 410–1313 & FAX: (416) 410–1806 www.nex–flow.com

TITLE: 1–1/4" THREADED ALUMINIUM RING VAC OUTLINE DRAWING

SIZE	CAGE CODE	DWG NO	RELEASE	REV
C	–	30002T	P	–

SCALE: 1:1 | CAD NO: – | SHEET 1 OF 1