



Ø0.26" [Ø6.50] X 3 HOLES THRU

Ø0.28" [Ø7.00] 2 HOLES, THRU ON 2.80" [71.12] PCD

PROPRIETARY
REPRODUCTION OR DISTRIBUTION
WITHOUT WRITTEN CONSENT OF
NEXFLOW™ IS PROHIBITED.

THIRD ANGLE PROJECTION	
MATERIAL	SS-304
FINISH	BUFFING

REQUIREMENTS—UNLESS OTHERWISE SPECIFIED	GENERAL
1. DIMS ARE IN INCHES [MM]	
2. DIMENSIONING AND TOLERANCING IN ACCORDANCE WITH ANSI Y14.5 (1982)	
3. MACHINE FINISH 125 MICRO INCH RMS	
4. INTERNAL RADI .015	
5. BREAK SHARP CORNERS .005 TO .015	
LIMITS	
1. LINEAR DIMS	
XXX = .005	
XX = .010	
X = .025	
2. ANGLES = ± 1/2°	
3. RUNOUT .010 THR	
4. HOLES IN ACCORDANCE WITH AND 10387	

CONTRACT NUMBER	—
CLIENT	—
CONTRACTOR	—
DRAWN	CHIRAG
DATE	30/01/2019
CHECKED	LES
PROJECT	—
PROJECT	—
STRESS	—
MANUFACTURING	—
THERMAL	—
MATERIALS	—
ELECTRICAL	—
MECHANISM	—

NEX FLOW AIR PRODUCTS CORP.			
10520 YONGE STREET, UNIT 35B-220, RICHMOND HILL, ON L4C 3C7 TEL.: (416) 410-1313 & FAX: (416) 410-1806 www.nex-flow.com			
TITLE			
MOUNTING BRACKET FOR 2" RING VAC			
SIZE	CAGE CODE	DWG NO	RELEASE
—	—	39004S	P 1
SCALE	CAD NO	SHEET	OF
1:1	—	1	1